



NOTES

- CONDITIONS MUST BE DRY FOR VOLTAGES ABOVE 45KV
- FOR VOLTAGES ABOVE 50KV USE 2EA068630

D	OMIT C & ADDED NOTES	MAM	2/19	JER	2/19
C	SUPERSEDED BY 2EW068630	MAM	3/11	JER	3/11
B	ADDED OPT 1	MAM	1/99	MJS	1/99
A	#3 ADDED FLANGE GROOVE	NLP	1/23/95	MJS	1/23/95
NO.	REVISION	BY	DATE	CKD	DATE

DESIGNED: JER
 CHECKED: MJS
 DRAWN: MAM 6/6/94
 NATIONAL ELECTROSTATICS CORPORATION
 MIDDLETON, WISCONSIN

2EW059082	2EA059571
2EW059081	2EA059570
ITEM 1	ASSEMBLY NO.
OPTIONS	

TOLERANCES AND FINISH UNLESS OTHERWISE SPECIFIED				
FRACTIONAL ±1/64"	.XXX ±.005	ANGLE ±.5°	MACH 125√	THIRD ANGLE PROJECTION
MATERIAL SEE PARTS LIST				

SCALE	1=1	DESIGNED	JER	FEEDTHRU, 50KV X N3.5 MOUNT, 8" OD SHIELD- ASSEMBLY
PART NO.	2EA059570	DWG NO.	C	LOC CV
			5-0-5957	